

READ INSTRUCTIONS BEFORE USE

SUDDEN UN-HOOKING CAN CAUSE SERIOUS INJURY

When fastening or releasing straps...

INCORRECT



Don't Do This
(Hook will slide off)


CORRECT



(Hook Fastened Securely)



Safety First
(Wear eye & head protection)

- The JB strap should be used for only securing tarp covers on trucks.
- Do not use the  straps as primary tie down with any application using a heavy or unstable load.
- Strap shall not be used for any lifting, raising, lowering or suspending purposes.
- Inspect each strap carefully before each tie down operation and discard any straps with nicks, cracks, cuts or any surface defects.
- Always protect strap from exposure to heated environments or hot surfaces.
- Do not replace hooks with hooks of inferior quality.
- Completely secure hooks during tie down. Strap should not be anchored around sharp edges or pulled over any abrasive surfaces.
- When pulling strap over the load always: wear eye protection; keep both feet firmly on the ground; keep other vulnerable body parts away from the potential rebound path.
- Ensure user is always working in clear space free from any moving vehicle or objects when fastening straps on a load.
- Failure to strictly follow these instructions and warnings can cause serious injury and death.



ISO 9001, 14001, 50001
CERTIFIED COMPANY

MAXIMUM STRETCH- NOT MORE THAN 50% ORIGINAL LENGTH

ADHERE TO CAUTION WARNING

WEAR EYE AND HEAD PROTECTION

USE EXTREME CARE